

**Rockwheeler Tri-Axle Side Tipper**



- DIMENSIONS:** 9940 x 2490 lead trailer  
 8000 x 2490 bowl  
 20m<sup>3</sup> bowl capacity
- SUSPENSION:** 9 leaf 9'1 mechanical overslung
- AXLES:** 10 Stud parallel bearing drum brake 285 PCD
- DOOR RAMS:** 36" cylinders
- TIP RAMS:** 5 ½" d/acting tipping cylinders
- KING PIN:** Removable 9mm bolt in
- FLOOR:** 5mm Hardox
- SIDES:** 5mm Hardox
- TYRES & RIMS:** 12 x 11R 22.5 on 10 Stud Steel Rims
- BRAKES:** ADR 38-04, yard release fitted (EBS)
- LANDING LEGS:** Dual speed
- TYRE CARRIER:** Dual tyre carrier
- REAR MEMBER:** V-orlandi coupling, fitted with air, electrics & hydraulics at rear
- LIGHTS:** Hella LED lights to ADR regulations
- MUDGUARDS:** Vinyl guards
- MUDFLAPS:** Fitted front and rear
- SANDTARP:** Manual
- FILTER:** Hydraulic inline high pressure filter fitted
- HUBOMETER:** Fitted
- LADDER:** Fitted to rear
- BEADBLASTING:** Prior to painting
- PAINT:** Two coats of primer, two coats of 2pak top coat
- MAX ATM:** 47 tonnes
- SIGNAGE:** Long Vehicle / Road Train sign to be fitted.  
 'Do Not Overtake' decal also supplied
- OPTIONS:** Aluminium rims, disc brakes, conmet axles,  
 air suspension, rubber mudguards, electric tarp

COMPLIANCE PLATE TO BE FITTED FOLLOWING TRAILER INSPECTION  
 FULL SERVICE CHECK AFTER 5000KM INCLUDING WHEEL ALIGNMENT  
 2 YEAR WARRANTY ON ALL STRUCTURAL COMPONENTS